

Square Twist Nails



- For use with joist hangers and restraint straps
- Can also be used for external cladding and/or felt
- The twisted shank gives superior pull out resistance
- Manufactured to BSI 202

Code	Length	Gauge	Finish	Box Weight	Average Nail Count Per Kg
NSSS0030375	30mm	3.75mm	Sherardised	25kg	350
NSSS0040375	40mm	3.75mm	Sherardised	25kg	300
NSSG0030375	30mm	3.75mm	Galvanised	25kg	350
NSSG0040375	40mm	3.75mm	Galvanised	25kg	300

Drive Screws



- Easily driven, twist threaded nail best suited for wood joints with substantial lateral or racking loads
- Particularly recommended for fastening hard woods and end-grain wood without splitting
- Used in conjunction with plastic roofing washers to secure corrugated sheeting
- Manufactured to BSI 202

Code	Gauge	Finish	Box Weight	Average Nail Count Per Kg
NDDG0075	75mm	Galvanised	25kg	59
NDDG0100	100mm	Galvanised	25kg	35
NDDG0115	115mm	Galvanised	25kg	31
NDDG0125	125mm	Galvanised	25kg	29
NDDG0150	150mm	Galvanised	25kg	26

Clout Nails



- A popular large headed general purpose nail
- The larger head stops any pull through on the material being fixed
- Applications include securing roofing felt, wire fencing, and roofing slates
- Manufactured to BSI 202

Code	Length	Gauge	Finish	Box Weight	Average Nail Count Per Kg
NCSG0020265	20mm	2.65mm	Galvanised	25kg	1035
NCSG0025265	25mm	2.65mm	Galvanised	25kg	815
NCSG0030265	30mm	2.65mm	Galvanised	25kg	660
NCSG0040265	40mm	2.65mm	Galvanised	25kg	570
NCSG0040335	40mm	3.35mm	Galvanised	25kg	350
NCSG0050265	50mm	2.65mm	Galvanised	25kg	430
NCSG0050335	50mm	3.35mm	Galvanised	25kg	290
NCSG0065265	65mm	2.65mm	Galvanised	25kg	330
NCSG0065375	65mm	3.75mm	Galvanised	25kg	180
NCSG0075375	75mm	3.75mm	Galvanised	25kg	150
NCSG0100450	100mm	4.50mm	Galvanised	25kg	75