ARTISAN (PRE-PACKS)

Tarpaulin



- Waterproof, shrinkproof, UV protected and rotproof tarpaulin with reinforced rope hems and rust proof aluminium eyelets
- For temporary roof protection, to act as a ground sheet or as a general utility cover
- Heavy duty, tear proof tarpaulin available (110gsm) with rubber reinforced corners

Code	Colour	Thickness	Size	Pack Quantity
RYTA080027035	Blue	80gsm	2.7 x 3.5 Metres	I
RYTA080035054	Blue	80gsm	3.5 x 5.4 Metres	I
RYTA080054070	Blue	80gsm	5.4 x 7.0 Metres	I
RYTA110035054	Blue	I I 0gsm	3.5 x 5.4 Metres	I

Barrier Fencing & Fencing Pins



- Hi-visibility plastic barrier mesh
- Ideal for construction work and temporary events
- Can be buried as a visual aid to protect underground services
- Use with steel fencing pin with lamp hook
- Industry standard, approx 10mm diameter

Code	Туре	Width	Roll Length	Finish	Rolls Per Pack		
WBFO501	Medium Duty Mesh	1000mm	50 Metres	Orange PVC	I		
WBFB501	Medium Duty Mesh	1000mm	50 Metres	Blue PVC	I		
WBFG501	Medium Duty Mesh	1000mm	50 Metres	Green PVC	I		
WBFY501	Medium Duty Mesh	1000mm	50 Metres	Yellow PVC	I		
Code	Туре	Length	Diameter	Finish	Pack Quantity		
WFPIN	Fencing Pins	1350mm	10mm	Self Colour	10		

Solid Braided Polished Cotton Sash Cord



- A quality classic cord with a round cross section and smooth polished surface
- Excellent over pulleys and exhibits good abrasion resistance due to the solid braided construction
- Cotton core for flexibility or nylon core available to order if an increased breaking load is required

Code	Colour	Туре	Hank Length	Diameter	Breaking Strain	Pack Quantity
RCRS08	Red Spot	No 8	12.5 Metres	6mm	85kg	8
RCSB08	Natural	No 8	12.5 Metres	6mm	85kg	8

Waxed Cotton Sash Cord



- A traditional 16 plait waxed cotton, low stretch sash cord
- High strength due to its polycore
- The wax finish provides a weatherproof, durable and smooth running cord, efficient over pulleys

Code	Colour	Туре	Hank Length	Diameter	Breaking Strain	Pack Quantity
RCW3	Natural	No 3	10 Metres	5mm	310kg	10
RCW4	Natural	No 4	10 Metres	6mm	340kg	10

Page 16 Version 1.01 Tel: 0118 945 5781 Fax: 0118 972 8241